




# MicroDock II

**automated instrument  
docking station**

## Cost effective calibration and bump test management

The most cost effective way to manage the calibration and bump testing of BW's portable gas detectors is through the MicroDock II automated test and calibration system. Fully portable and easily expandable, the MicroDock II requires no computer and provides simultaneous management of up to ten modules. Minimize expenses and maximize productivity with the MicroDock II.



### Compatible detectors

- GasAlertMicroClip
- GasAlertMicro
- GasAlertMicro 5 Series
- GasAlertClip Extreme (2 and 3 Year)
- GasAlert Extreme

- Quick and easy compliance - automatically maintain accurate records
- Automatic bump testing, calibration, record keeping and charging
- One base station with one AC outlet supports up to ten modules to suit your application





**Wear yellow. Work safe.**

### MicroDock II Features:

- Fully automatic “hands-free” calibration and functional bump testing
- Automatically verifies performance of audible and visual alarms
- Stores and updates calibration records in the MicroDock II, as well as in datalogging instruments
- Entirely self-contained with no computer required
- Lightweight and fully portable with optional wall mount
- Operates via 6V line power or a set of four C-cell batteries
- Fully customizable

- Add extra self-contained docking modules to system via simple, plug-in connections—no external pressure transducers or gas lines necessary
- Simple, accurate record keeping and fleet management
- Verifies proper performance of detectors
- Reduces maintenance costs
- Multiple MicroDock II systems can be connected via a LAN
- Includes BW Fleet Manager software for easy data analysis
- Multi-language support in English, French, German, Spanish and Portuguese

<b>MicoDock II Specifications</b>	
<b>Size</b>	8.3 x 10.4 x 3.2 in. / 21.2 x 26.3 x 8.2 cm (base station plus one docking module)
<b>Power Supply</b>	6V wall adaptor or four C-cell batteries
<b>Real-time clock</b>	Provides time and date stamp for “last calibration” and “last bump test” data
<b>Data Storage</b>	Automatic (instrument and base station) MultiMediaCard data storage system
<b>Communications method</b>	Infrared communication between docking module and detector
<b>External interface</b>	USB 2.0 interface for PC (USB 2.0 full speed)
<b>Pump</b>	DC motor, micro-diaphragm; 6V PCB mount Flow rate 300 ml/min (typically)
<b>Solenoid</b>	Built-in (docking modules)
<b>Calibration gas connections</b>	1/8" SMC connect sub-miniature coupling 2 gas inlets (standard), 5 gas inlets (maximum)
<b>Detector configuration</b>	Automatic recognition of instrument and sensors User-settable with Fleet Manager II software
<b>Command Keys</b>	Base station - Menu navigation Docking module - One touch bump-test initiation - One touch calibration initiation - One touch data transfer ( <i>specific products</i> )
<b>LED indicators</b>	Yellow “TEST”, Green “PASS”, Red “FAIL”
<b>Ratings</b>	This device complies with the FCC Part 15 and ICES-003 Canadian EMI requirements. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) This device must accept any interference received, including interference that may cause undesired operation.
<b>Certifications and approvals</b>	 Ordinary Location approved IEC 61010 C22.2 No. 61010  European Conformity
<b>Warranty</b>	Full 2 year warranty

### Options and Accessories



Cal Gas Wall Mount



MicroDock II portable system kit



Demand Flow Regulator



Anywhere USB


For a complete list of kits and accessories, please contact BW Technologies by Honeywell.

**MicroDock II with five modules** - choose any module combination with a maximum of ten docking modules, including six charging modules.



Note: Each gas cylinder connected to the system requires a individual demand flow regulator - sold separately

Locally available from



### Corporate Headquarters

2840 - 2 Avenue S.E.  
Calgary, AB, Canada T2A 7X9  
Phone: +1-403-248-9226

USA 1.888.749.8878  
Canada 1.800.663.4164  
Australia +61.3.9464.2770

Europe +44 (0)1295 700 300  
France +33 (0) 442 98 17 70  
Middle East +971-4-8871766

China +86 10 6786 7305  
S.E. Asia +65 6580 3468  
Other Countries +1-403-248-9226

[www.gasmonitors.com](http://www.gasmonitors.com)

[info@gasmonitors.com](mailto:info@gasmonitors.com)

DUE TO ONGOING RESEARCH AND PRODUCT IMPROVEMENT, SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE.